

Manual Motor Starters

Quick selection table ... IEC rating



Frame			32AF																			
Type	Current adjustable type		MMS-32S						MMS-32H													
	Instantaneous type		-						MMS-32HI													
Breaking capacity			Standard						High breaking													
Handle Type			Toggle						Rotary													
Number of poles			3						3													
Rated operational voltage (Ue)			Up to 690V						Up to 690V													
Rated frequency			50/60 Hz						50/60 Hz													
Rated insulation voltage (Ui)			690V						690V													
Rated impulse voltage (Uimp)			6kV						6kV													
Utilization category			IEC 60 947-2 (Breaker)						Cat. A													
			IEC 60 947-4 (Motor starter)						AC 3													
Mechanical endurance (Operating)			100,000						100,000													
Electrical endurance (Cycles)			100,000						100,000													
Max operating frequency per hour (Ope./h)			25						25													
Temperature compensation (Operation)			-20 ~ +60°C						-20 ~ +60°C													
Instantaneous short circuit release			13 × Ie max.						13 × Ie max.													
Overload protection			○						○													
Phase failure function			○						○													
Trip indicating function			×						×													
Test function			○						○													
Dimension(W×H×D)			45×105×54.4						45×105×60.3													
Weight (g)			320						360													
Rated breaking capacity (kA)	Rated operational current (Ie)	Thermal release Adjustment range (A)	220V 240V 230V		415V 400V		460V 440V		525V 500V		690V 600V		220V 240V 230V		415V 400V		460V 440V		525V 500V		690V 600V	
			Icu	Ics	Icu	Ics	Icu	Ics	Icu	Ics	Icu	Ics	Icu	Ics	Icu	Ics	Icu	Ics	Icu	Ics	Icu	Ics
			100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
0.16	0.16~0.16	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
0.25	0.16~0.25	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
0.4	0.25~0.4	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
0.63	0.4~0.63	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
1	0.63~1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100
1.6	1~1.6	100	100	100	100	100	100	100	100	100	3	3	100	100	100	100	100	100	100	100	100	100
2.5	1.6~2.5	100	100	100	100	100	100	100	50	38	3	3	100	100	100	100	100	100	100	100	8	8
4	2.5~4	100	100	100	100	50	38	15	11	3	3	3	100	100	100	100	100	100	100	100	8	8
6	4~6	100	100	100	100	15	11	10	8	3	3	3	100	100	100	100	100	100	100	6	6	6
8	5~8	100	100	100	100	15	11	10	8	3	3	3	100	100	100	100	50	38	50	38	6	6
10	6~10	100	100	50	38	15	11	6	5	3	3	3	100	100	100	100	50	38	50	38	6	6
13	9~13	100	100	50	38	10	8	6	5	3	3	3	100	100	100	100	50	38	42	32	6	6
17	11~17	50	38	20	15	10	8	6	5	3	3	3	100	100	50	38	20	15	10	8	4	4
22	14~22	40	30	15	11	8	6	6	5	3	3	3	100	100	50	38	20	15	10	8	4	4
26	18~26	40	30	15	11	8	6	5	4	3	3	3	100	100	50	38	20	15	10	8	4	4
32	22~32	30	22	10	5	6	4	5	4	3	3	3	100	100	50	38	20	15	10	8	4	4
40	28~40	20	15	10	5	5	3	4	3	2	2	2	100	100	40	30	15	11	8	6	3	3
50	34~50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
63	45~63	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
65	47~65	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
75	55~75	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
90	70~90	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
100	80~100	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

